

Industrial Bottle Jacks

▼ Shown: EBJ-4GC, EBJ-50GC, EBJL-15GC, EBJ-12GC



EBJ Series

Capacity:

1.5-100 tons

Stroke:


3.03-20.00 inches

- Lower handle effort reduces operator fatigue
- Fully serviceable
- Cast beam and cast pump linkage
- Pumping handle included on all models
- Safety relief valve to prevent overload
- Automatic by-pass port to prevent over-extension
- Wiper seal for extended life
- Chrome plating on pump and ram plungers



Screw Feature

Heat treated, adjustable extension screw with cleated saddle on selected EBJ models helps adjusting and prevents slipping.



Pump and Cylinder Sets

As an alternative to Industrial Bottle Jacks where the operator is required to stand remote from the jacking point, see the range of pump and cylinder sets.

Page: 58

Jack Capacity	Stroke	Model Number	Screw Extension	Minimum Height	Maximum Height	Plunger Diameter	Saddle Diameter	Base Dimensions	Weight
(tons)	(in)		(in)	(in)	(in)	(in)	(in)	L x W (in)	(lbs)
1.5	18.00	*EBJL-15GC	–	21.72	39.72	.88	.75	3.63 x 5.00	12.8
2	3.74	EBJ-2GC	2.76	6.89	13.39	.87	.83	4.02 x 3.78	6.6
3	20.00	*EBJL-3GC	–	26.31	46.31	1.12	1.12	4.25 x 5.50	22.0
4	4.72	EBJ-4GC	2.76	7.68	15.16	1.11	1.03	4.41 x 4.13	9.3
6	5.12	EBJ-6GC	3.15	8.27	16.54	1.34	1.19	4.72 x 4.49	12.1
8	5.51	EBJ-8GC	3.15	8.66	17.32	1.50	1.34	4.92 x 4.69	13.7
12	6.10	EBJ-12GC	3.15	9.45	18.70	1.70	1.58	5.31 x 5.12	17.6
12	3.03	*EBJS-12GC	1.69	6.10	10.83	1.70	1.58	5.31 x 5.12	14.6
15	5.91	EBJ-15GC	3.15	9.45	18.50	1.89	1.70	5.71 x 5.43	20.7
20	6.10	EBJ-20GC	3.15	9.84	19.09	2.09	1.82	6.10 x 5.71	25.1
20	3.11	*EBJS-20GC	1.61	6.50	11.22	2.09	1.82	6.10 x 5.71	19.8
30	6.89	*EBJ-30GC	–	11.22	18.11	2.80	2.72	7.48 x 5.91	56.9
50	4.13	*EBJ-50GC	–	9.25	13.78	3.35	3.15	10.04 x 7.48	92.6
100	5.91	*EBJ-100GC	–	12.28	18.38	4.89	3.94	11.81 x 9.45	198.9

* Short bottle jack † Without extension screw
All EBJ Jacks meet or exceed: ANSI, PALD, CE