



## Optimum Torque Wrench and Pump Combinations

For optimum speed and performance Enerpac recommends the following system set-up with wrench-pump-hose combinations.

	ELECTRIC PUMPS				AIR DRIVEN PUMPS		TWIN HOSES
	PMU-Series		ZU4T-Series*		PTA-Series	ZA4T-Series*	THQ-Series THC-Series
	Page: 213		Page: 214		Page: 218	Page: 220	
<b>10,000 psi Torque Wrenches</b>	Flow at rated pressure: 20 in <sup>3</sup> /min 115V, 1 ph	Flow at rated pressure: 20 in <sup>3</sup> /min 230V, 1 ph	Flow at rated pressure: 60 in <sup>3</sup> /min 115V, 1 ph	Flow at rated pressure: 60 in <sup>3</sup> /min 230V, 1 ph	Flow at rated pressure: 20 in <sup>3</sup> /min	Flow at rated pressure: 60 in <sup>3</sup> /min	
<b>Model No.</b>							
	S1500	PMU-10427-Q	PMU-10422-Q	-	-	PTA-1404-Q	-
	S3000						
	S6000	-	-	ZU4208TB-Q	ZU4208TE-Q	-	ZA4204TX-Q
	S11000						
	S25000						
	W2000	PMU-10427-Q	PMU-10422-Q			PTA-1404-Q	-
	W4000						
	W8000	-	-	ZU4208TB-Q	ZU4208TE-Q	-	ZA4204TX-Q
	W15000			ZU4208TI-Q	ZU4208TI-Q		
<b>11,600 psi Torque Wrenches</b>							
<b>Model No.</b>							
	SQD-25-I	PMU-10427	PMU-10422	-	-	PTA-1404	-
	SQD-50-I						
	SQD-75-I			ZU4208TB-E	ZU4208TE-E	-	ZA4204TX-E
	SQD-100-I	-	-		ZU4208TI-E		
	SQD-160-I						
	SQD-270-I						
	HXD-30	PMU-10427	PMU-10422	-	-	PTA-1404	-
	HXD-60						
	HXD-120	-	-	ZU4208TB-E	ZU4208TB-E	-	ZA4204TX-E
	HXD-240			ZU4208TI-E	ZU4208TI-E		

\* ZU4T and ZA4T are available in other configurations not listed in this chart.

### 1/4" Torque Wrench Spin-on Couplers

For use with 10,000 psi S- and W-series torque wrenches, THQ-series hoses and torque wrench pumps with suffix "Q".



Model Numbers			
Complete Set	Female Half	Male Half	
T-630	TR-630	TH-630	



### IMPORTANT!

Always make sure that the torque scale on the pump matches the torque wrench size for accurate torque settings.



### Call Enerpac!

For other combinations, consult your Enerpac bolting expert or your authorized Enerpac distributor.