

# Hydraulic Vertical Lifting Wedge

▼ LW-16 with SB-2 and optional LWB-1



- Requires very small access gap of only 10 mm
- Lifting force 16 ton at 700 bar hydraulic pressure
- Each step can spread under full load
- Straight vertical lifting
- Unique interlocking wedge design: no first step bending and risk of slipping out
- Single-acting, spring return cylinder
- Lifting wedge LW-16 includes safety block SB-2
- Includes RC-Series Cylinder with CR-400 coupler.

## LW Series

Maximum Lifting Force:

**16 ton**

Lifting Stroke:

**21 mm**

Tip Clearance / Maximum Spread\*:

**10 mm / 81,5 mm**

Maximum Operating Pressure:

**700 bar**



### Split-Flow Manifolds

Split Flow Valves to control two or four lifting wedges simultaneously.

AM-21 with 3 ports 3/8" NPTF  
AM-41 with 5 ports 3/8" NPTF.

Page: 128





### Best Match Hand Pump

To power your Enerpac Lifting Wedge, the Enerpac P-392 Hand Pump or P-392FP Foot Pump is an ideal choice.

Page: 68

▼ For lifting heavy equipment with minimum floor clearance the LW-16 is the ideal tool.



Maximum Lifting Force ton (kN)	Lifting Stroke (mm)	Model Number	Tip Clearance (mm)	Maximum Operating Pressure (bar)	Oil Capacity (cm <sup>3</sup> )	 (kg)
16 (157)	21	LW-16	10	700	78	9,0

Use optional stepped block LWB-1 to increase wedge lifting height by 30 mm.

\* Using LWB-1.