

# Crimping Tool

## HHT SERIES

**13-14 Ton**  
700 bar

The industry standard; durable, long-lasting hand hydraulic tools.

### COMPRESSION TOOLS FOR U-OR SHELL-TYPE DIES

- Two-speed pump for rapid ram advance\*
- High-strength fiberglass handles
- C-shaped head with 360° rotation for ease of accessibility\*\*
- Capacity for all U- or shell-type dies
- Twist handle release
- High-pressure safety relief valve
- Push-button system for ease of die insertion and removal
- With Carrying Bag

#### C12-TON-B

- C-shaped head with 180° rotation for ease of accessibility
- Trigger release handle



HYDRAULIC TOOLS

Tool Model	Crimping Force (tons)	Operating Pressure (bar)	Jaw Opening (mm)	Crimping Capacity (mm <sup>2</sup> )	Overall Length (mm)	Overall Depth (mm)	Head Width (mm)	Tool Weight (kg)
<b>C12-TON-B</b>	11,9	700	24,1	see below	579	76,2	217,5	6,1
<b>C12-HHT-B</b>	11,9	700	24,1	see below	579	76,2	219,5	6,1
<b>C14-HHT-B</b>	12,7	700	38,1	350	591	78,7	213	7,8

Copper	C12-HHT Crimping Capacity Aluminum	ASCR (Al+Cu+St)
No. 8 stranded through 260 mm <sup>2</sup> grounding terminals and splices	No. 8 stranded through 380mm <sup>2</sup> terminals	No. 6 stranded through 280mm <sup>2</sup> 26/7 stranding
No. 8 stranded through 125 mm <sup>2</sup> grounding taps and 3/4" ground rod	No. 8 stranded through 175 mm <sup>2</sup> splices	
No. 8 stranded through 380 mm <sup>2</sup> insulated and uninsulated terminals		

\* C12-Ton-B is a single stage pump.

\*\* C12-Ton-B Head rotates 180°