



## Description:

- Powerful: 6.5 tonne, 10 tonne and 15 tonne capacity.
- Proven: Thousands in use around the world.
- Well Engineered: Servicing and repairs easily undertaken.
- Safe: Relief valve prevents overloading.
- Compact and Lightweight: Ideal portable tool.
- Versatile: Operates in any orientation, totally enclosed and suitable for use in dusty conditions.
- Easy to Operate: Lift/lowering controlled easily by operating lever.

Product Code	8104H		1105002		1105003	
Capacity	6.5 tonne		10 tonne		15 tonne	
Oil Capacity	0.10 Litres	0.17 Pints	0.13 Litres	0.23 Pints	0.27 Litres	0.48 Pints
Jack Weight	3.6 kg	8 lbs	6.3kg	13.9 lbs	10.0 kg	22 lbs
Dimensions	mm	ins	mm	ins	mm	ins
A - Base Width	76	2.99	76	3	92	3.62
B - Base Depth	158	6.22	171	6.73	197	7.75
C - Closed Height	140	5.51	182	7.17	230	9.06
D - Stroke	75	2.95	115	4.5	152	5.98
E - Max Depth	190	7.48	207	8.15	236	9.29
F - Centre Ram to Face	33.3	1.31	40	1.57	48	1.89
Ram Diameter	30	1.18	38	1.5	47.5	1.87
Service Kit Number	995052		995053		995054	



HI-PRESS HYDRAULICS LTD  
RIVERSIDE WORKS,  
FORGE ROAD, WHALEY BRIDGE,  
HIGH PEAK, SK23 7HY

T: 01663 735089 - F: 01663 735090  
sales@hi-press.co.uk

HI-PRESS HYDRAULICS LTD  
UNIT 2, HALL HOUSE IND EST,  
NEW HUTTON, KENDAL,  
CUMBRIA, LA8 0AH

T: 01539 734005 - F: 01539 734006  
cumbria@hi-press.co.uk